

ABSTRACT

Asia-Pacific Conference on FRP in Structures (APFIS 2007)
12-14 December 2007, Hong Kong
<http://www.hku.hk/apfis07/>

Bond and Splice Behavior of a CFRP Strengthening System for Steel Structures

Mina Dawood*, Murthy Guddati and Sami Rizkalla

North Carolina State University,

mmdawood@ncsu.edu

ph: (919) 513-2040

fax: (919) 513-1765

Constructed Facilities Laboratory, Campus Box 7533,
2414 Campus Shore Dr., Raleigh, NC, 27695-7533USA

This paper summarizes a comprehensive experimental program and finite element modeling study undertaken to investigate the bond and splice behavior of carbon fiber reinforced polymer (CFRP) materials used for strengthening steel structures. The experimental program consisted of six CFRP double-lap shear coupons and ten steel beams which incorporated a CFRP lap-splice joint at midspan. The double-lap shear coupon tests incorporated different plate end configurations in an attempt to reduce the bond stress concentrations and consequently help increasing the joint capacity. The steel beams were tested to investigate the behavior of the splice joints under flexural loading. Splice plate lengths ranging from 200 mm to 800 mm were tested using various plate end configurations including square, reverse tapered and rounded plate ends. Mechanical anchorage of the splice joints, using transverse CFRP wraps and specially fabricated steel clamps, were tested to examine their effectiveness in resisting the peeling stresses. The results of the experimental program indicate that the presence of a reverse tapered plate end can help to significantly reduce the stress concentration and increase the capacity of bonded lap-splice joints. The results also demonstrate that careful detailing of the splice joints and the mechanical anchorage are essential to ensure the effectiveness of the joints.

A 3-D linear finite element analysis is used to model the behavior of the tested beams. The model was capable to accurately predict the bond stress distribution for splice joints with both square and reverse tapered plate ends. The calibrated finite element model was used to study various parameters believed to affect the bond behavior and the splice mechanisms. Based on the research findings, simple design recommendations are proposed to facilitate the proper design of CFRP splice joints for the CFRP strengthening system proposed for steel structures.

* Corresponding author

Please indicate which topic area your paper falls under by placing a X in the appropriate line of the right hand column of the following ‘Working Groups’ or ‘General Sessions’ tables

Working Groups

Bond Behaviour of FRP in Structures	
FRP-Strengthened Metallic Structures	X
FRP Bridge Decks	

General Sessions

(Special sessions may be formed for a topic area depending on the number of papers received)

Materials and products	
Strengthening of concrete, timber and masonry structures	
Strengthening of historical structures	
Confinement	
Seismic retrofit	
Concrete structures reinforced or prestressed with FRP	
Ductility of FRP strengthened or reinforced concrete structures	
All FRP structures	
Fire, impact and blast loading	
Durability and long-term performance	
Structural health monitoring and intelligent sensing	
Field applications and case studies	
Codes, standards, and design guidelines	
Other	